

PVC elevator belting

Monoply PVC elevator belts are oil and fat resistant and are temperature resistant between -15 °C and 80 °C. They are normally suitable for the foods industry. Color: white. Also available for the sugar industry.


PVC elevator belting				
Type	Top layers	Belt thickness	Weight kg/m2	Recommended pulley Ø
400	1,5 + 1,5	5 mm	6,25	250 mm
630	1,5 + 1,5	7 mm	8,75	400 mm
800	2,0 + 2,0	9 mm	11,25	500 mm
1.000	2,0 + 2,0	11 mm	13,75	500 mm
1.600	3,0 + 3,0	14 mm	17,50	630 mm

Elevator bucket bolts

Elevator bucket bolts in accordance with DIN 15237 are hot pressed and available in M7, M8, M10, and M12, zinc plated or in stainless steel.

Small head bucket bolts are available in M6, M7, and M8, zinc plated or in stainless steel.

Bucket bolts in accordance with DIN 15237 (in mm)		
Bolt diameter	Length	Head diameter
M 7	20 - 25 - 30 - 35	24
M 8	20 - 25 - 30 - 35 - 40 - 45 - 50	28
M 10	25 - 30 - 35 - 40 - 45 - 50 - 55 - 60	30
M 12	25 - 30 - 35 - 40 - 45 - 50 - 55 - 60 - 65	42



Besides, both versions are available with standard nuts, (nyloc) locknuts, flat or domed washers, and an Allen key head variety.

Bucket bolts (small head, in mm)		
Bolt diameter	Length	Head diameter
M 6	15 - 20 - 25 - 30	18
M 7	15 - 17 - 20 - 25 - 30 - 35	21
M 8	20 - 25 - 30 - 35	24

